



DIRECT-BURIAL

12VAC Transformer

FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- COMPRESSION MOLDED, FIBERGLASS REINFORCED POLYESTER COMPOSITE HOUSING
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- RESISTANT TO RUST, CORROSION, OILS, GASOLINE, & DETERGENTS
- PRIMARY WIRING COMPARTMENT & ANTI-SIPHON BARRIER
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.

REQUIREMENTS



- LISTED TO UL STANDARD 1838 FOR LANDSCAPE LIGHTING
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

	CLASS 1	CLASS 1
PART NUMBER	1030-TL (100 Watt)	1031-TL (300 Watt)
PRIMARY VOLTAGE	120VAC-1A MAX	120VAC-3A MAX
OUTPUT VOLTAGE	12-15VAC-8.3A MAX	12-15VAC-25A
BREAKERS	1x10A	1x25A
FREQUENCY	60 Hz	60 Hz
DIMENSIONS	12" x 7.5" x 6"	12" x 7.5" x 6"
WEIGHT	20 LBS.	22 LBS.