

InvisiLED® Palette Outdoor

24V Outdoor Color Changing LED Tape Light

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Color changing 24V system for any and all outdoor accent lighting applications. Uses the latest LED technology water sealed in silicone cased tape, while still delivering crisp, quality light and effortless navigation of curves.

FEATURES

- IP-68 rated, allows for submersion up to five feet
- Power supply is UL and CUL listed
- Wet location listed
- DMX controller option (consult factory)
- Select from any color to visibly change an interior design
- Switch to 3500K white light with the push of a button
- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 6" at the end of a run
- Unique tape section connections ensure even LED spacing and no dark spots
- Four mounting options provided for differentsurfaces
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS


- Construction:** Flexible, silicone cased tape light.
Indicating marks on back for field cutting.
- Power Supply:** Remote and plug-in electronic Class 2 transformers.
120VAC 50/60Hz input, 24V 96W output.
- Light Source:** 12 LEDs per foot
- Dimming:** Dimmable using an LED-TO24-WS wireless controller.
- Operating Temp:** -4°F – 122°F (-20°C – 50°C), relative humidity 95%.
- Standards:** UL & CUL listed for wet locations.

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Length	Light Color
LED-TCO	1.5	1 1 foot	RGB Color Changing
		5 5 feet	
		10 10 feet	

LED-TCO-___-RGB

Example: **LED-TCO-5-RGB**



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760


InvisiLED® Palette Outdoor

24V Outdoor Color Changing LED Tape Light




WAC LIGHTING

Responsible Lighting®











Class 2 Power Supply (Required)

Type	Model	Input	Output	Max Run	Dim	
Remote	 EN-O24100-RB2-T	120 - 277VAC	24VDC / 96W	40 feet	NO	<i>Class 2 rated Includes a 6 foot lead wire</i>

Controller

Master Controller		LED-TO24-CM	4" x 2" x 1½"	<i>Powers one run up to 40'. Connects and controls all slave controllers for runs over 40'.</i>
Slave Controller		LED-TO24-CS	4" x 2" x 1½"	<i>Connects to Master Controller for runs over 40'. Uses a separate 120V power supply. Powers up to another 40', a Slave Controller is needed for every 40' extension.</i>
Wireless Controller		LED-TO24-WS	4" x 2½" x 5/8"	<i>Wireless connection to Master Controller. Use to switch from color changing to white light Play/Pause the color changing effect Control the brightness and speed of the color changing effect Uses 2 AAA batteries.</i>

Accessories

Clear Channel		LED-TO24-CH5	5 feet	<i>Rigid, non-flexible channel for mounting to a straight, solid surface.</i>
Mounting Clip 1		LED-TO24-C1	10 pcs	<i>For installation on non-flat surfaces where there is no edge contact. 2 clips per ft are recommended for straight runs.</i>
Mounting Clip 2		LED-TO24-C2	10 pcs	<i>For installation on non-flat surfaces, allows for contact on one edge. 2 clips per ft are recommended for straight runs.</i>
Mounting Clip 3		LED-TO24-C3	10 pcs	<i>For installation on non-flat surfaces, allows for contact on both edges. 2 clips per ft are recommended for straight runs.</i>
Joiner Cable		LED-TO24-IC6 LED-TO24-IC12 LED-TO24-IC72 LED-TO24-IC120	6 in 12 in 72 in 120 in	<i>Extends distance between Power Supply and Master Controller.</i>
Signal wire		LED-TO24-SW60 LED-TO24-SW120	5 feet 10 feet	<i>Connects Master Controller and Slave Controller.</i>
DMX Signal Wire		LED-TO24-MW60 LED-TO24-MW120	5 feet 10 feet	<i>Connects DMX system to Master Controller.</i>
RGB Joiner Cable		LED-TO24-IC6-RGB LED-TO24-IC12-RGB LED-TO24-IC72-RGB LED-TO24-IC120-RGB	6 in 12 in 72 in 120 in	<i>Use to connect two sections of InvisiLED® Outdoor Palette tape.</i>
3-Way "Y" Connector		LED-TO24-Y-RGB		<i>Connects tape sections</i>
4-Way "X" Connector		LED-TO24-X-RGB		<i>Connects tape sections</i>
End cap		LED-TO24-EC		<i>Use to terminate every run to protect against contaminants. Seal cut end with silicone after adding end cap.</i>