

# **Folsom**

## Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	<b>Delivered Lumens</b>	Title 24
WS-W23610 10"	<b>3000</b> K 90	BZ Bronze	6.5W	630	120	Yes

Example: WS-W23610-BZ

•For 277V special order, add an "F" before the finish: WS-W23610F-BZ

For custom requests please contact customs@waclighting.com

#### DESCRIPTION

Die-cast aluminum forged into stripes encasing an inner etched opal glass create a unique design suitable for many outdoor commercial and residential applications. Folsom is availablein two finish options, and two sizes.

## **FEATURES**

- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

#### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10%
Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum with acrylic diffuser



## **FINISHES:**




Bronze

## **LINE DRAWING:**

## REPLACEMENT PARTS

RPL-GLA-23610-01 - Outer glass for WS-W23610 RPL-GLA-23610-02 - Inner glass for WS-W23610





# **Folsom**

## Outdoor Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	<b>LED Lumens</b>	<b>Delivered Lumens</b>	Title 24
WS-W23614 14"	<b>3000K</b> 90	BZ Bronze	12W	965	163	Yes

Example: WS-W23614-BZ

•For 277V special order, add an "F" before the finish: WS-W23614F-BZ

For custom requests please contact customs@waclighting.com

## DESCRIPTION

Die-cast aluminum forged into stripes encasing an inner etched opal glass create a unique design suitable for many outdoor commercial and residential applications. Folsom is availablein two finish options, and two sizes.

## **FEATURES**

- Title 24 may not be available for all finishes, check for availability
- ACLED driverless technology
- 5 year warranty

#### **SPECIFICATIONS**

Color Temp: 3000K

**Input:** 120 VAC,50/60Hz

**CRI:** 90

Dimming: ELV: 100-10%
Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum with acrylic diffuser

## **FINISHES:**



Bronze

## **LINE DRAWING:**

## **REPLACEMENT PARTS**

RPL-GLA-23614-01 - Outer glass for WS-W23614 RPL-GLA-23614-02 - Inner glass for WS-W23614

